

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
15 July 2004 (15.07.2004)

PCT

(10) International Publication Number  
**WO 2004/059006 A1**

- (51) International Patent Classification<sup>7</sup>: C12Q 1/68, G01N 33/543
- (21) International Application Number: PCT/JP2003/016227
- (22) International Filing Date: 18 December 2003 (18.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2002-374695 25 December 2002 (25.12.2002) JP  
2002-374794 25 December 2002 (25.12.2002) JP
- (71) Applicant (for all designated States except US): CA-SIO COMPUTER CO., LTD. [JP/JP]; 6-2, Hon-machi 1-chome, Shibuya-ku, Tokyo 151-8543 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): OGURA, Jun [JP/JP]; 1202, Fussa, Fussa-shi, Tokyo 197-0011 (JP). ISHIDA, Hideaki [JP/JP]; 23-3-1403, Naka-cho 1-chome, Musashino-shi, Tokyo 180-0006 (JP).
- (74) Agents: ARAFUNE, Hiroshi et al.; 5F, Nikko Kagurazaka Bldg., 18, Iwatocho, Shinjuku-ku, Tokyo 162-0832 (JP).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OPTICAL DNA SENSOR, DNA READING APPARATUS, IDENTIFICATION METHOD OF DNA AND MANUFACTURING METHOD OF OPTICAL DNA SENSOR



(57) Abstract: The advantage is to provide a DNA reading apparatus which can sense fluorescence even if the sensitivity of a CCD image sensor or a photomul is low and can be constructed in a compact size. An optical DNA sensor having: a solid imaging device, and a plurality types of DNA probe each including nucleotide sequence and being arrayed and fixed on a surface of the solid imaging device.

WO 2004/059006 A1